

VINOOTHÈQUE CAFÉ

DUAL ZONE UNDERCOUNTER WINE CELLAR



BENEFITS

- A perfect balance of commercial quality, performance and luxe design
- Equipped with advanced high performance inverter compressor cooling for consistent stable temperature
- Library quiet. You will hardly know its on
- Dual zone for storage and service for red, white and sparkling wine
- Commercial grade stainless steel trim triple pane glass door with anti-UV protection
- Sliding Beechwood shelving with stainless steel trim

FEATURES

SHELVING	Rolling
INTERIOR LIGHTING	Side Mounted White LED
CONTROLS	Electronic Touch
TEMPERATURE DISPLAY	White LED
GLASS DOOR	Triple Pane
REVERSIBLE DOOR	Yes
SECURITY LOCK	Yes
WARRANTY	1-Year Parts & Labor 3-Years Sealed System
CHARCOAL FILTER	Yes
LEVELING LEGS	4

GENERAL INFORMATION

BOTTLE CAPACITY*	Maximum 46 Bottles
USABLE VOLUME	4.9 Cu. Ft.
INSTALLATION TYPE	Free Standing / Built-In
VENTING	Front
TEMPERATURE ZONES	2
TEMPERATURE RANGE	Upper Zone: 54°F – 68°F Lower Zone: 41°F – 54°F
DOOR STYLE	Seamless Stainless Steel
HANDLE	Stainless Steel Pro Handle
STORAGE RACKS – QUANTITY	4
STORAGE RACKS – TYPE	Beechwood
STORAGE RACKS – FRONT TRIM	Stainless Steel
SHELF EXTENSION	76% (4 pcs)
SUGGESTED AMBIENT TEMPERATURE (F)	50°F – 109°F

*Maximum bottle capacity may vary depending on bottle size and shelf configuration.

ZONES	DOOR TRIM	HINGE	SHELF TRIM	MODEL
2	Stainless Steel	Right Hinge	Natural Wood with Stainless Steel Trim Shelves	261 02 51 03
2	Stainless Steel	Left Hinge	Natural Wood with Stainless Steel Trim Shelves	261 02 51 04

ACCESSORIES

	MODEL
Vinothèque Wine Cellar – Charcoal Filter	261 99 44
Vinothèque Wine Cellar – Charcoal Filter (Set of 2)	261 99 88
Vinothèque Wine Cellar – Charcoal Filter (Set of 4)	261 99 66

VINOTHÈQUE CAFÉ

DUAL ZONE UNDERCOUNTER WINE CELLAR



DIMENSIONS & WEIGHT

WINE CELLAR DIMENSIONS	34¼"H x 24"W x 24"D*
MINIMUM DIMENSIONS OF BUILT-IN AREA	34¾"H x 25"W x 27¾"D
GROSS SHIPPING WEIGHT	Approximately 127 lbs.
NET WEIGHT	Approximately 114 lbs.

*Handle adds 2" to depth.

ELECTRICAL

ELECTRICAL REQUIREMENTS	115V / 60HZ
RATED POWER INPUT	162 Watts
RATED CURRENT	1.8 Amps
REFRIGERANT	R600A, 1.41 oz.
ENERGY CONSUMPTION	253 kwh/year
PLUG TYPE	Right Angle NEMA 5-15P Plug with SJT 3X18AWG Cord
BREAKER SIZE	15 Amp Line
DECIBEL RATING	42 dB(A)

Multiple Unit Note: If there is more than one cellar on a line, a 20 Amp circuit is required.

VINOTHÈQUE CAFÉ DUAL ZONE UNDERCOUNTER WINE CELLAR · PARTS, FEATURES AND DIMENSIONS

