

VINOOTHÈQUE CAFÉ

150-BOTTLE DUAL ZONE MAX WINE CELLAR WITH ULTRA-EFFICIENT STEADY-TEMP™ COOLING



BENEFITS

- A perfect balance of commercial quality, performance and luxe design
- Three patented VinoView shelves** showcase your prized wine.
 - Eleven rolling shelves to maximize storage capacities
- Dual Zone MAX storage gives you the ability to MAXimize the lower zone for long-term aging and set the top zone for cooler service...or set both compartments to the same temperatures for a traditional Dual Zone cellar
- Our innovative 80/20 split Dual Zone MAX gives you the MAXimum space to store and age your collection while the top zone can be set to the perfect service temperature for your white, rosé & sparkling wines
- Equipped with Ultra-Efficient Steady-Temp™ Cooling Technology – premium inverter cooling technology, ensuring the most consistent temperature
- Library quiet, you will hardly know its on
- Commercial grade stainless steel trim glass door with anti-UV protection
- Sliding Beechwood shelving with stainless steel trim

FEATURES

SHELVING	Rolling
INTERIOR LIGHTING	Side Mounted White LED
CONTROLS	Electronic Touch
TEMPERATURE DISPLAY	White LED
GLASS DOOR	Triple Pane
REVERSIBLE DOOR	Yes
SECURITY LOCK	Yes
WARRANTY	1-Year Parts & Labor 3-Years Sealed System
CHARCOAL FILTER	Yes
LEVELING LEGS	4

GENERAL INFORMATION

BOTTLE CAPACITY*	Maximum 150 Bottles
USABLE VOLUME	13.7 Cu. Ft.
INSTALLATION TYPE	Free Standing / Built-In
VENTING	Front
TEMPERATURE ZONES	2
TEMPERATURE RANGE	Upper Zone: 41°F – 68°F Lower Zone: 41°F – 68°F
DOOR STYLE	Seamless Stainless Steel or Edge-To-Edge Black Glass
HANDLE	Stainless Steel Flat Bar
STORAGE RACKS – QUANTITY	3 VinoView and 11 Rolling
STORAGE RACKS – TYPE	Stainless Steel: Natural Wood Edge-To-Edge: Black Wood
STORAGE RACKS – FRONT TRIM	Stainless Steel
SHELF EXTENSION	77% (14 pcs)
SUGGESTED AMBIENT TEMPERATURE (F)	50°F – 109°F

*Maximum bottle capacity may vary depending on bottle size and shelf configuration.
**U.S. Design Patent No. D826,995

Note: In order for a dual zone unit to function at optimum level, the upper compartment requires to be set at least 4-Degrees (F) lower than the lower compartment.

ZONES	DOOR TRIM	HINGE	SHELF TRIM	MODEL
2	Stainless Steel	Right Hinge	Stainless Steel	261 02 44 03 K
2	Stainless Steel	Left Hinge	Stainless Steel	261 02 44 04 K
2	Edge-To-Edge Black Glass	Right Hinge	Stainless Steel	261 03 44 03 K
2	Edge-To-Edge Black Glass	Left Hinge	Stainless Steel	261 03 44 04 K

ACCESSORIES

ACCESSORIES	MODEL
VinoView Shelves – Stainless Steel Trim Shelves in Natural Wood (Set of 3)	261 02 99 64
VinoView Shelves – Stainless Steel Trim Shelves in Black Wood (Set of 3)	261 03 99 64
Vinothèque Wine Cellar – Charcoal Filter	261 99 44
Vinothèque Wine Cellar – Charcoal Filter (Set of 2)	261 99 88
Vinothèque Wine Cellar – Charcoal Filter (Set of 4)	261 99 66

VINOTHÈQUE CAFÉ

150-BOTTLE DUAL ZONE MAX WINE CELLAR WITH ULTRA-EFFICIENT STEADY-TEMP™ COOLING



DIMENSIONS & WEIGHT

WINE CELLAR DIMENSIONS	67¾"H x 23½"W x 28¼"D*
MINIMUM DIMENSIONS OF BUILT-IN AREA	68¼"H x 24½"W x 31¼"D
GROSS SHIPPING WEIGHT	Approximately 295 lbs.
NET WEIGHT	Approximately 240 lbs.

*Handle adds 2" to depth.

ELECTRICAL

ELECTRICAL REQUIREMENTS	115V / 60HZ
RATED POWER INPUT	220 Watts
RATED CURRENT	1.9 Amps
REFRIGERANT	R600A, 1.58 oz.
ENERGY CONSUMPTION	250 kwh/year
PLUG TYPE	NEMA5-15P Plug with SJT 3X18AWG Cord
BREAKER SIZE	15 Amp Line
DECIBEL RATING	39 dB(A)

Multiple Unit Note: If there is more than one cellar on a line, a 20 Amp circuit is required.

VINOTHÈQUE CAFÉ 150-BOTTLE DUAL ZONE MAX WINE CELLAR • PARTS, FEATURES AND DIMENSIONS

